

Granville Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube VL 5W/30 is a fully synthetic engine oil formulated to provide outstanding performance levels both in terms of engine cleanliness and fuel economy. The product is recommended by Granville Oil & Chemicals Ltd for use in Volkswagen, Audi, Seat and Skoda engines requiring a VW specification oil. Hypalube VL 5W/30 is fully compatible with exhaust after treatment devices such as diesel particulate filters.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: C3
VW: 504.00 & 507.00
API: SN/CF
BMW: LL-04
MB: 229.51
Porsche: C30

PRODUCT BENEFITS

- * Effective environmental protection
- * Outstanding fuel efficiency
- * Excellent high & low temperature performance
- * Ensures lubricant performance over extended drain intervals

PRODUCT USAGE

VAG engine types.

DIRECTIONS FOR USE

As recommended by the engine manufacturer



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1127	5020618011279
5 Litre	1128	5020618011286
20 Litre	1129	5020618011293
199 Litre	1132	5020618011323



Granville Hypalube VL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	10.07
Total Base Number	ASTM D2896	mg KOH/g	7		8.33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Pour Point	ASTM D97	°C		-36	
NOACK Volatility	ASTM D5800	%		<10	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			59.81
Density	ASTM D792	@ 15°C			0.852

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

